

BSZ-100



Características

- **Sub-Zero version.**
- Gondola-type design with group at the bottom.
- Interior and exterior made of metal sheet that provide a great robustness.
- Bottom with drain.
- Skirting board in black enamelled steel, with reinforcement for the group in the central part.
- Two injected plastic doors that act as a thermal barrier.
- Includes a divider for the interior.
- Low-maintenance condenser.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Uniform cold distribution thanks to the excellent design of the cooling system.
- Palletized 4 units per pallet.

Opciones

- Exterior customizable.
- Inner material according to specifications.
- Unitary palletized.

External dimensions (mm)

1042 x 606 x 910

Net weight (kg)

56

Internal net volume (Lt)

141

Capacity 33 cl cans / 33 cl bot (pcs)

234 / 144

Lateral serigraphy dimensions (mm)

516 x 602

Transport 40' container / 13m truck

91 / 104

24h energy consumption (kW/h)

2,39

Climatic class

CC2 (32°C/65%HR)

Temperature range (°C)

-2,7 / -1

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Front serigraphy dimensions (mm)

1035 x 602