

The sub zero efficold chest cooler is specially developed to keep your drinks below zero with the lowest energy consumption, and identical customisation options as the other models.

Important element for any beverage distributor both for its usefulness and its impact on marketing. We provide the latest technological innovations and the best design for the client.



## **Características**

- Sub-Zero version.
- Gondola-type design with group at the bottom.
- Interior and exterior made of metal sheet that provide a great robustness.

  • Bottom with drain.
- Skirting board in black enamelled steel, with reinforcement for the group in the central part.
- One injected plastic door that act as a thermal barrier.
- Low-maintenance condenser.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m3
- Temperature control by digital thermostat with automatic
- Uniform cold distribution thanks to the excellent design of the cooling system.
- Palletized 4 units per pallet.

## **Opciones**

- Exterior customizable.
- Inner material according to specifications.
- Unitary palletized.

## **Datos técnicos**

| External dimensions (mm)            | 430 x 606 x 910  |
|-------------------------------------|------------------|
| Net weight (kg)                     | 34               |
| Internal net volume (Lt)            | 71               |
| Capacity 250 ml pets (pcs)          | 65               |
| Lateral serigraphy dimensions (mm)  | 516 x 602        |
| Transport 40' container / 13m truck | 176 / 192        |
| 24h energy consumption (kW/h)       | 1,47             |
| Climatic class                      | CC2 (32°C/65%HR) |
| Temperature range (°C)              | -2,7 / -1        |
| Refrigerant                         | R-600a           |
| Voltage / frequency                 | 230v / 50Hz      |
| Front serigraphy dimensions (mm)    | 423 x 602        |