

CC-90 - CONFERENCE COOLER

Características

- **Ideal product for meeting rooms or places that require low noise pollution thanks to its reduction of the sound level to less than 40db.**
- **Rear socket**, which among other uses, allows you to connect a coffee maker and leave it on the upper table.
- **Double interior LED light** vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a **great robustness**.
- **Triple glass door** mounted on an aluminium profile and handle in the front.
- Three internal shelves included and eight external wooden and PVC shelves to favor a wide product display.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by **digital thermostat** with automatic defrost.
- **Uniform cold distribution** thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Door lock.
- Low-maintenance condenser.
- **Wheels to facilitate movement.**
- Unitary palletized.

Opciones

- Exterior customizable.
- Printed and/or illuminated logo on the glass.

External dimensions (mm)

565 x 540 x 1180

Net weight (kg)

75

Internal net volume (Lt)

85

Capacity cans 33cl / pet 500ml (pcs)

96 / 44

Door serigraphy dimensions (mm)

306 x 958

Transport 40' container / 13m truck

76 / 92

24h energy consumption (kW/h)

1,88

Climatic class

CC2-K4 (32°C/65%HR)

Temperature range (°C)

0 / +6,6

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Sound level (dBa)

<40

