

DS-2W



Características

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle either inlaid on the side.
- Three shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Two rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Doors with self-closing and opening fixation system.
- Unitary palletized.

Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).

External dimensions (mm)

523 x 498 x 1543

Net weight (kg)

69

Internal net volume (Lt)

125

Capacity 33 cl cans / 50 cl pets (pcs)

120 / 60

Lateral grid serigraphy dimensions (mm)

417 x 417

Front glass serigraphy dimensions (mm)

353 x 947

Lateral glass serigraphy dimensions (mm)

588 x 947

Transport 40' container / 13m truck

0 / 0

24h energy consumption (kW/h)

1,66

Climatic class

CC1 (25°C/60%HR)

Temperature range (°C)

0 / +8

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Front grid serigraphy dimensions (mm)

435 x 421