

DS-4W 1.9



Características

- Four interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle either inlaid on the side.
- Eight shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Four rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Doors with self-closing and opening fixation system.
- Unitary palletized.

Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).

External dimensions (mm)

879 x 480 x 1909

Net weight (kg)

152

Internal net volume (Lt)

238

Capacity 33 cl cans / 50 cl pets (pcs)

400 / 200

Lateral grid serigraphy dimensions (mm)

273 x 765

Front glass serigraphy dimensions (mm)

1480 x 374

Lateral glass serigraphy dimensions (mm)

1480 x 309

Transport 40' container / 13m truck

42 / 62

24h energy consumption (kW/h)

2.5

Climatic class

CC1 (25°C/60%HR)

Temperature range (°C)

+2 / +10

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Front grid serigraphy dimensions (mm)

273 x 434