

# EERM-250



## Características

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass doors mounted on a plastic profile and handle in the front.
- Two shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m<sup>3</sup>.
- Temperature control by digital thermostat with automatic defrost.
- Four feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Door lock as standard.
- Low-maintenance condenser.
- Unitary palletized.

## Opciones

- Exterior customizable.
- Printed logo in the glass.
- Energy Management Device (EMD).

External dimensions (mm)

920 x 570 x 900

Net weight (kg)

80

Internal net volume (Lt)

218

Capacity 33 cl cans / PET 500ml (pcs)

228 / 132

Lateral serigraphy dimensions (mm)

460 x 855

Glass serigraphy dimensions (mm)

370 x 718

Transport 40' container / 13m truck

76 / 96

24h energy consumption (kW/h)

2,76

Climatic class

CC2-K4 (32°C/65%HR)

Temperature range (°C)

+2 / +8

Refrigerant

R-600a

Voltage

230v

Frequency

50Hz