EF2-22MU



Our back-bar coolers are a reference in the international market because of its quality, reliability and thanks to our collaboration with the most prestigious beverages brands in this range for over 30 years.

Efficold's equipment highlights for the low energy consumption and they are designed exclusively for our customers to enhance their brand at the sales point.



Características

- Four flat shelves.
- Four feet adjustable in height.
- Digital thermostat and automatic defrost.
- Automatic evaporation of defrost water.
- Low maintenance condenser.
- Double LED internal illumination (only on when door is open).
- Ecological injected polyurethane insulation free of CFCs, density 40kg/m³.
- Ultra low energy consumption.Low Noise level of 49dB(A).
- Self closing door system for perfect sealing at all times.
- Door remains open when at 90° for easy loading.
- An IoT ready device.

Opciones

- Exterior customizable.
- Reverse door.

Datos técnicos

External dimensions (mm)	1150 x 560 x 850
Net weight (kg)	72
Internal net volume (Lt)	272
Capacity 33 cl cans / bot. 20cl (pcs)	365 / 312
Refrigeration power (W)	167
Noise level (db)	49
Transport 13m truck	88
24h energy consumption (kW/h)	1,57
Climatic class	CC2-K4 (32°C/65%HR)
Temperature range (°C)	+2 / +8
Refrigerant	R-600a
Voltage	230V
Frequency	50Hz