

FAST LANE 1500



Características

- Interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle in the front.
- Four shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by analog thermostat.
- Four rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Door with self-closing.
- Low-maintenance condenser.
- Palletized four units per pallet.

Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.

External dimensions (mm)

502 x 482 x 1510

Net weight (kg)

62

Internal net volume (Lt)

138

Capacity 33 cl cans / 50 cl pets (pcs)

180 / 90

Lateral serigraphy dimensions (mm)

496 x 266

Transport 40' container / 13m truck

84 / 104

24h energy consumption (kW/h)

-

Climatic class

CC2 (32°C/65%HR)

Temperature range (°C)

0 / +8

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Front serigraphy dimensions (mm)

357 x 1476