

FIFO FGC-TT



Características

- Triple interior LED light to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Five vertical product levels, which help consumers to take drinks at the same time quickly.
- Adjustable shelves to avoid cannibalization between brands.
- Double glass door mounted on an aluminium profile and handle either inlaid on the side.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Four feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Door lock.
- Unitary palletized.

Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).

External dimensions (mm)

587 x 523 x 1088

Net weight (kg)

51

Internal net volume (Lt)

77

Capacity PET 500ml (pcs)

65

Lateral serigraphy dimensions (mm)

437 x 1068

Transport 40' container / 13m truck

120 / 130

24h energy consumption (kW/h)

2,32

Climatic class

CC1 (25°C/60%HR)

Temperature range (°C)

+2 / +8

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Noise level (db)

40,4