

ICEH-87



Características

Compact design, maximum capacity and great interior visibility.

- Interior horizontal LED light to maximise product visibility.
- Interior and exterior made of sheet steel for great robustness.
- Double glazed door mounted on aluminium profile and handle embedded in the front.
- Ecological CFC-free injected polyurethane insulation, density 40kg/m³.
- Temperature control by digital thermostat with automatic defrosting.
- Four height adjustable feet.
- Uniform distribution of cold inside thanks to the excellent design of the ventilated cooling system and evaporator.
- Automatic evaporation of defrost water.
- Unitary palletising.

Opciones

- Exterior customisation.
- Energy Management Device (EMD).
- LED illuminated base.
- Door with soft-closing system to close the door slowly and safely.
- Internal separators.
- Big Capacity (BC) version with 71Lt of internal capacity and 126 units of 33cl cans.

External dimensions (mm)

583 x 655 x 870

Net weight (kg)

59

Internal net volume (Lt)

52

Capacity 33 cl cans (pcs)

84

Frequency (Hz)

50Hz

Transport 40' container / 13m truck

90 / 114

24h energy consumption (kW/h)

2,04

Climatic conditions

CC1 (25°C/60%HR)

Refrigeration power (KW)

0,253

Temperature range (°C)

+3 / +8

Refrigerant

R-600a

Voltage (v)

230