

# ICEL-76



## Características

**Compact design, maximum capacity and great interior visibility.**

- Interior horizontal LED light to maximise product visibility.
- Interior and exterior made of sheet steel for great robustness.
- Double glazed door mounted on aluminium profile and handle embedded in the front.
- Ecological CFC-free injected polyurethane insulation, density 40kg/m<sup>3</sup>.
- Temperature control by digital thermostat with automatic defrosting.
- Four height adjustable feet.
- Uniform distribution of cold inside thanks to the excellent design of the ventilated cooling system and evaporator.
- Automatic evaporation of defrost water.
- Unitary palletising.

## Opciones

- Customisable exterior.
- Printed and/or illuminated logo on the glass.
- Energy Management Device (EMD).
- Door lock.
- Door with soft-closing system to close the door slowly and safely.
- Internal separators (see photo).

External dimensions (mm)

603 x 655 x 700

Net weight (kg)

57

Internal net volume (Lt)

56

Capacity 33 cl cans (pcs)

84

Frequency (Hz)

50Hz

Transport 40' container / 13m truck

90 / 114

24h energy consumption (kW/h)

1,8

Climatic class

CC1 (25°C/60%HR)

Refrigeration power (kW)

0,253

Temperature range (°C)

+3 / +8

Refrigerant

R-600a

Voltage (v)

230