



Características

Compact and open design, maximum capacity and great interior visibility.

- Interior LED light horizontally arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle in the front.
- Ecological injected polyurethane insulation free of CFCs, density 40kg/m³.
- Temperature control by digital thermostat with automatic defrost.
- Four feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the cooling system.
- Automatic evaporation of defrost water.
- Door with self-closing and opening fixation system.
- Door lock.
- Low-maintenance condenser.
- Unitary palletized.

Opciones

- Exterior customizable.
- Energy Management Device (EMD).
- LED backlight on the base.

External dimensions (mm)

593 x 678 x 737

Net weight (kg)

58

Internal net volume (Lt)

45

Capacity 33 cl cans (pcs)

63

Front serigraphy dimensions (mm)

580 x 385

Transport 40' container / 13m truck

90 / 114

24h energy consumption (kW/h)

3,12

Climatic class

CC1-K4 (25°C/60%HR)

Temperature range (°C)

+3 / +8

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Refrigeration power (kW)

0,253