

# MC-1000



## Características

- Interior LED light vertically arranged to maximize product visibility, without ultraviolet radiation.
- Interior and exterior in steel sheet that provides great robustness.
- Equipped with four shelves, with a maximum load of 40kg. As standard, the shelves are coated with antibacterial plastic
- Ecological injected polyurethane insulation free of CFCs, density 40kg/m<sup>3</sup>.
- Double glass door equipped with hinges, automatic return system and opening fixing.
- Two height-adjustable front feet and four rear rollers for easy movement.
- Uniform distribution of the cold inside thanks to the excellent design of the ventilated cooling system and its evaporator with anti-corrosion coating.
- Temperature control by digital thermostat with automatic defrost system, that also allows to regulate the humidity level and the inner temperature.
- Automatic evaporation of defrosting water.
- Electronic humidostat.
- Low maintenance condenser.
- UV air sterilization.
- Activated carbon filter.
- Door lock as standard.
- Unitary palletized.

## Opciones

- Exterior black finish or stainless steel AISI 304.
- Shelves and trays with electropolished finish.
- Horizontal bracket with hooks to hang the inner product.
- Trays for salt from the Himalayas.
- Supplementary stand.

External dimensions (mm)

700 x 750 x 1665

Internal dimensions (mm)

595 x 615 x 1424

Net weight (kg)

120

Internal net volume (Lt)

496

Illumination

Yes - LED

Transport 13m truck (pcs)

48

24h energy consumption (kW/h)

1,7

Climatic class

4 (30°C / 55% HR)

Temperature range (°C)

0 / +20

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Humidity level (%)

60 to 90