

ML-705

Características

- Triple interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle in the front.
- **Easyfill configurable system** with shelves and neck-hanger, which allows a faster replacement and the best facing of the product. The standard equipment is four shelves and two neck hangers.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Door with self-closing system and opening fixation.
- Two rollers and three front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Low-maintenance condenser.
- Unitary palletized.

Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Personalized price-tags.

External dimensions (mm)

736 x 730 x 1672

Net weight (kg)

141

Internal net volume (Lt)

302

Capacity 33 cl cans (pcs)

253

Lateral serigraphy dimensions (mm)

653 x 1640

Transport 40' container / 13m truck

42 / 51

24h energy consumption (kW/h)

1,62

Climatic class

CC2-K4 (32°C/65%HR)

Temperature range (°C)

+1 / +9

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Front serigraphy dimensions (mm)

89 x 652

