ML-705



Our upright coolers are a reference in the international market because of its quality, reliability and thanks to our collaboration with the most prestigious beverages worldwide brands in this range for over 30 years.

Refrigerated cabinets are ideal for the exhibition of food, beverages and in general products that require conservation at a positive temperature.



Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Personalized price-tags.

Características

- Triple interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle in the front.
- Easyfill configurable system with shelves and neckhanger, which allows a faster replacement and the best facing of the product. The standard equipment is four shelves and two neck hangers.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Température control by digital thermostat with automatic defrost.
- Door with self-closing system and opening fixation.
- Two rollers and three front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Low-maintenance condenser.
- Unitary palletized.

Datos técnicos

| External dimensions (mm) | 736 x 730 x 1672 |
|-------------------------------------|---------------------|
| Net weight (kg) | 141 |
| Internal net volume (Lt) | 302 |
| Capacity 33 cl cans (pcs) | 253 |
| Lateral serigraphy dimensions (mm) | 653 x 1640 |
| Transport 40' container / 13m truck | 42 / 51 |
| 24h energy consumption (kW/h) | 1,62 |
| Climatic class | CC2-K4 (32°C/65%HR) |
| Temperature range (°C) | +1 / +9 |
| Refrigerant | R-600a |
| Voltage / frequency | 230v / 50Hz |
| Front serigraphy dimensions (mm) | 89 x 652 |