

ML-900



Características

- Triple interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass doors mounted on an aluminium profile and handle in the front.
- Six **shelves included with EasyFill system**, which allows a faster replacement and the best facing of the product.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Doors with self-closing system and opening fixation.
- Four rollers and three front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Low-maintenance condenser.
- Unitary palletized.

Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Personalized price-tags.

External dimensions (mm)

905 x 732 x 2015

Net weight (kg)

195

Internal net volume (Lt)

531

Capacity 33 cl cans / 50 cl pet (pcs)

888 / 444

Lateral serigraphy dimensions (mm)

670 x 1981

Transport 40' container / 13m truck

36 / 42

24h energy consumption (kW/h)

5,88

Climatic class

CC2-K4 (32°C/65%HR)

Temperature range (°C)

+1 / +9

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Front serigraphy dimensions (mm)

74 x 354