

NLX-76



Características

- Interior LED light horizontally arranged to maximize the product visibility.
- Interior made of thermoformed plastic and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on a plastic profile.
- Two shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by analog thermostat.
- Four feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Low-maintenance condenser.
- Palletized of four units per pallet.

Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).

External dimensions (mm)

495 x 450 x 670

Net weight (kg)

25

Internal net volume (Lt)

68

Capacity 33 cl cans / 33 cl bot (pcs)

65 / 38

Lateral serigraphy dimensions (mm)

384 x 555

Transport 40' container / 13m truck

176 / 264

24h energy consumption (kW/h)

1

Climatic class

CC2-K4 (32°C/65%HR)

Temperature range (°C)

+1 / +9

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Glass serigraphy dimensions (mm)

395 x 504