

Our positive display showcases are the perfect combination of our technical innovation with the best brand exposure. They are a benchmark in the market for their quality, reliability and for the collaboration of the most prestigious global beverage brands for 30 years.



## Características

- Interior LED light horizontally arranged to maximize the product visibility.
- Interior made of thermoformed plastic and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on a plastic profile.
- Two shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m<sup>3</sup>.
- Temperature control by analog thermostat.
- Four feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Low-maintenance condenser.
- Palletized of four units per pallet.

## Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).

## Datos técnicos

External dimensions (mm)	495 x 450 x 670
Net weight (kg)	25
Internal net volume (Lt)	68
Capacity 33 cl cans / 33 cl bot (pcs)	65 / 38
Lateral serigraphy dimensions (mm)	384 x 555
Transport 40' container / 13m truck	176 / 264
24h energy consumption (kW/h)	1
Climatic class	CC2-K4 (32°C/65%HR)
Temperature range (°C)	+1 / +9
Refrigerant	R-600a
Voltage / frequency	230v / 50Hz
Glass serigraphy dimensions (mm)	395 x 504