

RV-100



Características

- Internal LED light vertically arranged to maximize the product visibility.
- Exterior made of metal sheet that provide a great robustness and interior made of thermoformed plastic.
- Double glass door mounted on a plastic profile and handle either inlaid on the side.
- One shelf included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by analog thermostat.
- Four feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Low-maintenance condenser.
- Palletized four units per pallet.

Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Personalized price-tags.
- Door with self-closing system.
- Door with aluminium profile.

External dimensions (mm)

445 x 480 x 700

Net weight (kg)

35

Internal net volume (Lt)

56

Capacity 33 cl cans / 50 cl pets (pcs)

60 / 25

Lateral serigraphy dimensions (mm)

418 x 679

Transport 40' container / 13m truck

192 / 224

24h energy consumption (kW/h)

1.42

Climatic class

CC2-K4 (32°C/65%HR)

Temperature range (°C)

+1 / +9

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Glass serigraphy dimensions (mm)

380 x 535