

RV-180



Características

- Interior LED light vertically arranged to maximize the product visibility.
- Exterior made of metal sheet that provide a great robustness and interior in thermoformed plastic.
- Double glass door mounted on an aluminium profile and handle either inlaid on the side.
- Two shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Four feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Low-maintenance condenser.
- Palletized four units per pallet.

Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Analog thermostat.
- Door with self-closing system.

External dimensions (mm)

505 x 570 x 935

Net weight (kg)

42

Internal net volume (Lt)

130

Capacity 33 cl cans / 50 cl pets (pcs)

144 / 86

Lateral serigraphy dimensions (mm)

508 x 920

Transport 40' container / 13m truck

176 / 192

24h energy consumption (kW/h)

1,6

Climatic class

CC2-K4 (32°C/65%HR)

Temperature range (°C)

+1 / +9

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Glass serigraphy dimensions (mm)

455 x 788