

# RV-30



## Características

- Interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle either inlaid on the side.
- One shelf included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m<sup>3</sup>.
- Temperature control by digital thermostat with automatic defrost.
- Four feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Low-maintenance condenser.
- Palletized six units per pallet.

## Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Door with self-closing system.

External dimensions (mm)

362 x 428 x 491

Net weight (kg)

20

Internal net volume (Lt)

23

Capacity 33 cl cans / 50 cl pets (pcs)

28 / 16

Lateral serigraphy dimensions (mm)

381 x 509

Transport 40' container / 13m truck

228 / 312

24h energy consumption (kW/h)

0,826

Climatic class

CC1-K4 (25°C/60%HR)

Temperature range (°C)

+1 / +9

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Glass serigraphy dimensions (mm)

364 x 443