

RV-35 PLUS



Características

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle either inlaid on the side.
- Two shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Four feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Low-maintenance condenser.
- Palletized for units per pallet.

Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door with self-closing system.

External dimensions (mm)

431 x 466 x 655

Net weight (kg)

39

Internal net volume (Lt)

48,5

Capacity 33 cl cans / 50 cl pets (pcs)

70 / 35

Lateral serigraphy dimensions (mm)

381 x 630

Transport 40' container / 13m truck

192 / 312

24h energy consumption (kW/h)

1,16

Climatic class

CC2 (32°C/65%HR)

Temperature range (°C)

+2 / +6

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Glass serigraphy dimensions (mm)

348 x 547