

# RV-80



## Características

- Top horizontal LED light to maximize product visibility.
- Exterior and interior made of steel sheet providing great robustness.
- Triple glazed door mounted on aluminum profile with handle on the side.
- Equipped with two shelves.
- Polyurethane insulation injected with eco-friendly, CFC-free material, density 40kg/m<sup>3</sup>.
- Temperature control via digital thermostat with automatic defrost.
- Four adjustable height feet.
- Uniform cold distribution inside thanks to excellent design of ventilated cooling system and evaporator.
- Door equipped with hinges with automatic return system.
- Automatic defrost water evaporation.
- Low maintenance condenser.
- Four units per pallet.

## Opciones

- Customizable exterior.
- Printed and/or illuminated logo on glass.
- Energy Management Device (EMD).
- Lock.

External dimensions (mm)

500 x 550 x 780

Internal net volume (Lt)

86

Capacity 33 cl cans / 50 cl pets (pcs)

100 / 40

24h energy consumption (kW/h)

0.8

Lateral serigraphy dimensions (mm)

460 x 418

13m truck capacity (uts)

192

Energy rating

C

Climatic class

CC2-K4 (32°C/65%HR)

Temperature range (°C)

+1 / +9

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Glass serigraphy dimensions (mm)

418 x 664