RV-900



Our upright coolers are a reference in the international market because of its quality, reliability and thanks to our collaboration with the most prestigious beverages brands in this range for over 30 years.

Refrigerated cabinets are ideal for the exhibition of food, beverages and products in general that require conservation at a positive temperature.



- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Personalized price-tags.Shelves with FIFO system.

Características

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminum profile and handle in the front.
- Five shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m3
- Temperature control by digital thermostat with automatic defrost.
- Four rollers and two front feet adjustable in height.Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.

 • Automatic evaporation of defrost water.
- Doors with self-closing and opening fixation system.
- Low-maintenance condenser.
- Automatic evaporation of defrost water.
- Unitary palletized.

Opciones

Datos técnicos

| External dimensions (mm) | 905 x 752 x 2015 |
|--|-----------------------|
| Net weight (kg) | 195 |
| Internal net volume (Lt) | 685 |
| Capacity 33 cl cans / 50 cl pets (pcs) | 1056 / 528 |
| Lateral serigraphy dimensions (mm) | 670 x 1981 |
| Transport 40' container / 13m truck | 36 / 42 |
| 24h energy consumption (kW/h) | 5,88 |
| Climatic class | CC2-K4 (32°C/65%HR) |
| Temperature range (°C) | +1 / +9 |
| Refrigerant | R-600a |
| Voltage / frequency | 230v / 50Hz |
| Glass serigraphy dimensions (mm) | 354 × 74 |
| Refrigerant Voltage / frequency | R-600a 230v / 50Hz |