

RVC-1000



Características

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glazed door mounted on an aluminum profile and handle in the front.
- Eight shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Six rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Doors with self-closing system.
- Low-maintenance condenser.
- Unitary palletized.

Opciones

- Exterior and canopy customizable.
- Printed logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Personalized price tags.
- Available with R-600a or R-290 gas.

External dimensions (mm)

1250 x 725 x 2040

Net weight (kg)

106

Internal net volume (Lt)

665

Capacity 33 cl cans / 50 cl pets (pcs)

960 / 480

Lateral serigraphy dimensions (mm)

2018 x 629

Transport 40' container / 13m truck

27 / 30

24h energy consumption (kW/h)

4.53

Climatic class

CC2 (32°C/65%HR)

Temperature range (°C)

0 / +6.6

Refrigerant

R-290

Voltage / frequency

230v / 50Hz

Canopy serigraphy dimensions (mm)

1223 x 190