

RVC-101



Características

- Interior LED light vertically arranged to maximize the product visibility.
- Exterior made of metal sheet that provide a great robustness and interior in thermoformed plastic.
- Double glass door mounted on an aluminium profile and handle either inlaid on the side.
- One shelf included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by analog thermostat.
- Four feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Door with self-closing and opening fixation system.
- Low-maintenance condenser.
- Palletized four units per pallet.

Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Door with self-closing system.
- Door with aluminium profile.

External dimensions (mm)

445 x 480 x 865

Net weight (kg)

37

Internal net volume (Lt)

60

Capacity 33 cl cans / 50 cl pets (pcs)

75 / 35

Lateral serigraphy dimensions (mm)

418 x 838

Transport 40' container / 13m truck

192 / 224

24h energy consumption (kW/h)

1,66

Climatic class

CC2-K4 (32°C/65%HR)

Temperature range (°C)

+1 / +9

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Canopy serigraphy dimensions (mm)

425 x 177