



# RVC-235

## Características

- Interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle either inlaid on the side.
- Five shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m<sup>3</sup>.
- Temperature control by analog thermostat.
- Two rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Low-maintenance condenser.
- Unitary palletized.

## Opciones

- Exterior customizable
- Printed and /or illuminated logo in the glass.
- *Energy Management Device (EMD).*
- *Door lock.*
- *Personalized price-tags.*

External dimensions (mm)

480 x 671 x 1813

Net weight (kg)

82

Internal net volume (Lt)

208

Capacity 33 cl cans / 50 cl pets (pcs)

252 / 150

Lateral serigraphy dimensions (mm)

588 x 1763

Transport 40' container / 13m truck

66 / 75

24h energy consumption (kW/h)

2.37

Climatic class

CC2 (32°C/65%HR)

Temperature range (°C)

+2 / +6,6

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Canopy serigraphy dimensions (mm)

478 x 143