

RVC-280



Características

- Interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle in the front.
- Five shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Two rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Door with self-closing and opening fixation system.
- Low-maintenance condenser.
- Unitary palletized.

Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.

External dimensions (mm)

600 x 690 x 2000

Net weight (kg)

101

Internal net volume (Lt)

390

Capacity 33 cl cans / 50 cl pets (pcs)

525 / 261

Lateral serigraphy dimensions (mm)

575 x 1975

Transport 40' container / 13m truck

53 / 63

24h energy consumption (kW/h)

4,17

Climatic class

CC1-K4 (25°C/60%HR)

Temperature range (°C)

+1 / +9

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Canopy serigraphy dimensions (mm)

592 x 264