

RVC-300

Características

- Internal LED light vertically arranged to maximize the product visibility.
- Interior made of thermoformed plastic and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminum profile and handle either inlaid on the side.
- Four shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by analog thermostat.
- Two back rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Door with self-closing and opening fixation system.
- Automatic evaporation of defrost water.
- Low maintenance condenser.
- Palletized 1 unit per pallet.

Opciones

- Exterior customizable.
- Printed and / or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Personalized price-tags.

External dimensions (mm)

620 x 690 x 2000

Net weight (kg)

91

Internal net volume (Lt)

400

Capacity 33 cl cans / 50 cl pets (pcs)

518 / 250

Lateral serigraphy dimensions (mm)

590 x 1988

Transport 40' container / 13m truck

51 / 60

24h energy consumption (kW/h)

2,55

Climatic class

CC2-K4 (32°C/65%HR)

Temperature range (°C)

+1 / +9

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Canopy serigraphy dimensions (mm)

613 x 177

