

RVC-450

Características

- Interior LED light vertically arranged to maximize the product visibility.
- Exterior made of metal sheet that provide a great robustness and interior in thermoformed plastic.
- Double glass door mounted on an aluminium profile and handle either inlaid on the side.
- Five shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg/m³.
- Temperature control by digital thermostat with automatic defrost.
- Two rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Door with self-closing and opening fixation system.
- Low-maintenance condenser.
- Unitary palletized.

Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Personalized price-tags.

External dimensions (mm) 690 x 680 x 2025 Net weight (kg) 117 Internal net volume (Lt) 415 Capacity 33 cl cans / 50 cl pets (pcs) 580 / 240 Lateral serigraphy dimensions (mm) 580 x 1987 Transport 40' container / 13m truck 48 / 54 24h energy consumption (kW/h) 4,17 Climatic class CC1-K4 (25°C/60%HR) Temperature range (°C)

+1 / +9 Refrigerant R-600a Voltage / frequency 230v / 50Hz

Fake canopy serigraphy dimensions (mm) 610 x 177