

RVC-700

Características

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle either inlaid on the side.
- Five shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Four rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Unitary palletized.

Opciones

- Exterior and canopy customizable.
- Printed logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Personalized price tags.
- Door with self-closing system.

External dimensions (mm)

785 x 797 x 2100

Net weight (kg)

155

Internal net volume (Lt)

600

Capacity 33 cl cans (pcs)

800

Lateral serigraphy dimensions (mm)

687 x 2073

Transport 40' container / 13m truck

42 / 48

24h energy consumption (kW/h)

4.3

Climatic class

CC2 (32°C/65%HR)

Temperature range (°C)

+2 / +10

Refrigerant

R-290

Voltage / frequency

230v / 50Hz

Canopy serigraphy dimensions (mm)

765 x 210

