

# RVC-800



## Características

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glazed door mounted on an aluminum profile and handle in the front.
- Five shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m<sup>3</sup>.
- Temperature control by digital thermostat with automatic defrost.
- Two rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Doors with self-closing system.
- Low-maintenance condenser.
- Unitary palletized.

## Opciones

- Exterior and canopy customizable.
- Printed logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Personalized price tags.
- Available with R-600a or R-290 gas.

External dimensions (mm)

875 x 690 x 2000

Net weight (kg)

132

Internal net volume (Lt)

598

Capacity 33 cl cans / 50 cl pets (pcs)

816 / 408

Lateral serigraphy dimensions (mm)

575 x 1975

Transport 40' container / 13m truck

39 / 42

24h energy consumption (kW/h)

4.51

Climatic class

CC1 (25°C/60%HR)

Temperature range (°C)

+2 / +10

Refrigerant

R-600a (R-290 optional)

Voltage / frequency

230v / 50Hz

Canopy serigraphy dimensions (mm)

867 x 254