

RVCS-1000

Características

- Slide doors version.
- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robutness.
- Double glazed door mounted on an aluminum profile.
- Eight shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Six rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Doors with self-closing system.
- Low-maintenance condenser.
- Unitary palletized.

Opciones

- Exterior and canopy customizable.
- Printed logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Personalized price tags.
- Available with R-600a or R-290 gas.

External dimensions (mm)
1250 x 715 x 2040
Net weight (kg)
166
Internal net volume (Lt)
665
Capacity 33 cl cans / 50 cl pets (pcs)
960 / 480
Lateral serigraphy dimensions (mm)
2018 x 685
Transport 40' container / 13m truck
25 / 30

24h energy consumption (kW/h) 5,14 Climatic class CC1 (25°C/60%HR) Temperature range (°C) 0 / +6,6 Refrigerant R-290 Voltage / frequency

230v / 50Hz Canopy serigraphy dimensions (mm) 1170 x 190