

SLIM BULLET



Características

- **Full-glass door** with double glazing and **handle incorporated** in the upper part of the glass.
- **Interior LED light** to maximise product visibility.
- Interior and exterior in steel sheet to provide **great robustness**.
- Equipped with a shelf.
- Ecological CFC-free injected polyurethane insulation, density 40kg/m³.
- **Uniform cold distribution** inside thanks to the excellent design of the cooling system.
- Temperature control by **digital thermostat** with automatic defrost.
- Automatic evaporation of defrost water.
- Low maintenance condenser.
- Palletising of 18 units per pallet.

Opciones

- Customisable exterior.
- Illuminated door.
- Screen-printed logo on the glass.
- Personalised price holders.

External dimensions (mm)

233 x 565 x 466

Net weight (kg)

14

Internal net volume (Lt)

18

Capacity 33 cl cans / cans 50cl (pcs)

12

Lateral serigraphy dimensions (mm)

520 x 430

Transport cont. 40'

660

Capacity 33 cl Slim cans / cans 25cl (pcs)

16

24h energy consumption (kW/h)

0,78

Climatic class

CC2-K4 (32°C/65%HR)

Temperature range (°C)

+2 / +8

Refrigerant

R-600a

Voltage / frequency

230V / 50Hz