

SLIM FREEZER



Características

- Double interior LED light vertically arranged to maximize the product visibility.
- Metallic interior and exterior that provide a great robustness.
- Triple glass door mounted on an aluminum profile and handle either inlaid on the side.
- Static evaporator of six levels that guarantee a homogenous cold distribution, integrating the function of shelves, which five are available for product.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat.
- Two back rollers and two front feet adjustable in height.
- Drain inside the chamber to evacuate the water during the evaporator cleaning.
- Palletized of four units per pallet.

Opciones

- Customizable exterior.
- Custom price holder.
- Lock to prevent opening.
- Energy Management Device (EMD)

External dimensions (mm)

400 x 480 x 1870

Net weight (kg)

68

Internal net volume (Lt)

99

Refrigeratiion power (W)

309

Lateral serigraphy dimensions (mm)

355 x 1845

Transport 40' container / 13m truck

100 / 104

24h energy consumption (kW/h)

3,2

Climatic class

CC7 (35°C/75%HR)

Temperature range (°C)

-22 / -18

Refrigerant

R-290

Voltage / frequency

230v / 50Hz

Canopy serigraphy dimensions (mm)

395 x 142