

SLIM M 205

Características

- Double interior LED light vertically arranged to maximize the product visibility.
- Exterior and interior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminum profile and handle either inlaid on the side.
- Five shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Two back rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Door with self-closing and opening fixation system.
- Drain inside the chamber.
- Palletized six units per pallet.

Opciones

- Customizable exterior color with finishes in stainless steel, wood, plastic, cooper ... with canopy printed on the door.
- Door lock.
- Customized price-tags.
- Energy Management Device (EDM).
- **Fresh version** in gray with aluminum profiles, handle in silver color and black grid.
- **Prime version** with interior and exterior in black and full vision glass door without profiles

External dimensions (mm)

435 x 465 x 1980

Net weight (kg)

70

Internal net volume (Lt)

205

Capacity 33 cl cans / 50 cl pets (pcs)

200 / 100

Lateral serigraphy dimensions (mm)

411 x 1950

Transport 40' container / 13m truck

100 / 132

24h energy consumption (kW/h)

2.96

Climatic class

CC1-K2 (25°C/60%HR)

Temperature range (°C)

+2 / +8

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Door serigraphy dimensions (mm)

430 x 1655

