

SZ-345



Características

- Double internal LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Glass door mounted on an aluminium profile and handle either inlaid on the side.
- Five shelves included. – Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Two rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Door with self-closing system.
- Unitary palletized.

Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.

External dimensions (mm)

500 x 615 x 1985

Net weight (kg)

82

Internal net volume (Lt)

345

Capacity 33cl cans (pcs)

380

Glass serigraphy dimensions (mm)

423 x 1582

Transport 40' container / 13m truck

66 / 75

24h energy consumption (kW/h)

3.31

Climatic class

CC2 (32°C/65%HR)

Temperature range (°C)

-3.5 / -1

Refrigerant

R-290

Voltage / frequency

230v / 50Hz

Lateral serigraphy dimensions (mm)

557 x 1946