

ST-385



Características

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle either inlaid on the side.
- Five shelves included.
- Leveling feet in the front and rollers in the rear.
- Ecological injected polyurethane insulation free of CFCs, density 40kg/m³.
- Temperature control by digital thermostat with automatic defrost.
- Four rollers and two front feet adjustable in height. Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Door with self-closing and opening fixation system.
- Low-maintenance condenser.
- Unitary palletizing.

Opciones

- Exterior and canopy in door customizable.
- Lock to prevent opening.
- Custom price holder.
- Energy Management Device (EMD).

Dimensions (mm)

600 x 660 x 1950

Net weight (kg)

98

Net internal volume (lt)

347

Capacity 33cl cans / 50cl pet (pcs)

574 / 287

Climatic class

CC2-K2 (32°C - 65% HR)

Temperature range (°C)

-1 / +6

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Lateral serigraphy dimensions (mm)

619 x 1962

Transport cont. 40' / 13m truck (uts)

57 / 66