

SZ-181



Características

- Internal LED light vertically arranged to maximize the product visibility.
- Interior made of thermoformed plastic and exterior made of metal sheet that provide a great robustness.
- Glass door mounted on an aluminium profile and handle on the side.
- Two shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Four feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Low-maintenance condenser.
- Unitary palletized.

Opciones

- Exterior customizable-
- Printed and / or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.
- Door with self-closing system.

External dimensions (mm)

505 x 570 x 1140

Net weight (kg)

48

Internal net volume (Lt)

123

Capacity 33cl cans (pcs)

45

Canopy serigraphy dimensions (mm)

445 x 177

Transport 40' container / 13m truck

192 / 216

24h energy consumption (kW/h)

3.53

Climatic class

CC2 (32°C/65%HR)

Temperature range (°C)

-2.7 / -1

Refrigerant

R-600a

Voltage / frequency

230v / 50Hz

Lateral serigraphy dimensions (mm)

508 x 1086