

SZ-235



Características

- Interior LED light to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle either inlaid on the side.
- Four shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Four rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Low-maintenance condenser.
- Unitary palletized.

Opciones

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.

External dimensions (mm)

483 x 673 x 1690

Net weight (kg)

80

Internal net volume (Lt)

227

Capacity 33 cl cans / 50 cl pets (pcs)

252 / 294

Lateral serigraphy dimensions (mm)

586 x 1640

Transport 40' container / 13m truck

-

24h energy consumption (kW/h)

3.3

Climatic class

CC2 (32°C/65%HR)

Temperature range (°C)

-3 / -1

Refrigerant

R-290

Voltage / frequency

230v / 50Hz

Glass serigraphy dimensions (mm)

379 x 1248