SZ-300



Características

• Interior LED light vertically arranged to maximize the product visibility.

 Interior made of thermoformed plastic and exterior made of metal sheet that provide a great robustness.

• Double glass door mounted on an aluminium profile and handle either inlaid on the side.

Four shelves included.

 Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.

 Temperature control by digital thermostat with automatic defrost.

 Four rollers and two front feet adjustable in height.

 Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.

Automatic evaporation of defrost water.

• Door with self-closing system.

Low-maintenance condenser.

• Unitary palletized.

Opciones

560 x 1656

Exterior customizable.

Printed and /or illuminated logo in the glass.

Energy Management Device (EMD).

• Door lock.

External dimensions (mm) 620 x 655 x 1850 Net weight (kg) Internal net volume (Lt) 400 Capacity 33 cl cans (pcs) 518 Lateral serigraphy dimensions (mm) 590 x 1825 Transport 40' container / 13m truck 51 / 60 24h energy consumption (kW/h) 4,1 Climatic class CC2 (32°C/65%HR) Temperature range (°C) -3 / -1 Refrigerant R-290 Voltage / frequency 230v / 50Hz Glass serigraphy dimensions (mm)