

VAH-340-V



Características

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Triple glass door mounted on an aluminium profile and handle either inlaid on the side.
- Four shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Four rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system.
- Automatic evaporation of defrost water.
- Door with self-closing system.
- Unitary palletized.

Opciones

- Ventilated or static cooling according to customer needs.
- Door lock.
- Customizable exterior.
- Logo illuminated on the glass.
- Customizable price tags.
- Energy management device (EMD).

External dimensions (mm)

530 x 750 x 1960

Net weight (kg)

110

Internal net volume (Lt)

238

24h energy consumption (kW/h)

11.9

Transport 40' container / 13m truck

54 / 69

Refrigeration Power (W)

452

Temperature range (°C)

-24 / -14

Refrigerant

R-290

Voltage / frequency

230v / 50Hz

Lateral serigraphy dimensions (mm)

668 x 1926

Glass serigraphy dimensions (mm)

435 x 1480