

VAH-400-V



Características

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Triple glass door mounted on an aluminium profile and handle either inlaid on the side.
- Four shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Two rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system.
- Automatic evaporation of defrost water.
- Door with self-closing system.
- Unitary palletized.

Opciones

- Ventilated or static cooling according to customer needs.
- Door lock.
- Customizable exterior.
- Logo illuminated on the glass.
- Customizable price tags.
- Energy management device (EMD).

External dimensions (mm)

710 x 640 x 1960

Net weight (kg)

128

Internal net volume (Lt)

296

Refrigeration power (W)

452

Canopy serigraphy dimensions (mm)

680 x 215

Transport 40' container / 13m truck

51 / 57

24h energy consumption (kW/h)

-

Climatic conditions

CC1 (25°C/60%HR)

Temperature range (°C)

-24 / -14

Refrigerant

R-290

Voltage / frequency

230V / 50Hz

Lateral serigraphy dimensions (mm)

572 x 1929