VRA-1500

Características

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that • provide a great robustness. Three shelves included.
- ٠
- Canopy with LED illumination.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³. Temperature control by digital thermostat with
- automatic defrost.
- Four wheels to facilitate the movement.
- Night cover to improve energy efficiency and reduce thermal losses.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Unitary palletized.

Opciones

- Exterior customizable.
- Energy Management Device (EMD).
- Personalized price-tags.
- External body covered with wood.

External dimensions (mm) 500 x 625 x 1468 Net weight (kg) 78 Ínternal net volume (Lt) 143 Capacity 33 cl cans / 50 cl pets (pcs) 96 / 48 Lateral serigraphy dimensions (mm) 436 x 1388 Transport 40' container / 13m truck 63 / 75 24h energy consumption (kW/h) 8,67 Climatic class CC1-K4 (25°C/60%HR) Temperature range (°C) +1/+9 Refrigerant R-290 Voltage / frequency 230v 7 50Hz Canopy serigraphy dimensions (mm)

492 x 174

