

EF3-222MU

Our refrigerated wall displays are a reference in the international market for their quality and reliability, thanks to the collaboration with the most prestigious beverage brands in this range for more than 30 years.

Our back-bar coolers are a reference in the international market because of its quality, reliability and thanks to our collaboration with the most prestigious beverages brands in this range for over 30 years.

Features

- Six flat shelves.
- Six feet adjustable in height.
- Digital thermostat and automatic defrost.
- Automatic evaporation of defrost water.
- Low maintenance condenser.
- Triple LED internal illumination (only on when door is open).
- Ecological injected polyurethane insulation free of CFCs, density 40kg/m³.
- Ultra low energy consumption.
- Low Noise level of 53dB(A).
- Self closing door system for perfect sealing at all times.
- Door remains open when at 90° for easy loading.
- An IoT ready device.

Options

- Exterior customizable.
- Reverse door.



Reliability



Hydrocarbons



Energy Saving



Customization

Technical Data

External dimensions (mm)	1989 x 512 x 850
Net weight (kg)	95
Internal net volume (Lt)	469
Capacity 33 cl cans / bot. 20cl (pcs)	675 / 558
24h energy consumption (kW/h)	1,9
Climatic class	CC2-K4 (32°C/65%HR)
Temperature range (°C)	+2 / +8

* (width x depth x height)

Refrigerant	R-600a
Voltage	230v
Frequency	50Hz
Refrigeration power (W)	162
Noise level (db)	53
Transport 13m truck	48