

EF3-22GDMU

Our back-bar coolers are a reference in the international market because of its quality, reliability and thanks to our collaboration with the most prestigious beverages brands in this range for over 30 years.

Efficold`s equipment highlights for the low energy consumption and they are designed exclusively for our customers to enhance their brand at the sales point.

Features

- Four flat shelves.
- Four feet adjustable in height.
- Digital thermostat and automatic defrost.
- Automatic evaporation of defrost water.
- Low maintenance condenser.
- Double LED internal illumination (only on when door is open).
- Ecological injected polyurethane insulation free of CFCs, density 40kg/m³.
- Ultra low energy consumption.
- Low Noise level of 53dB(A).
- Self closing door system for perfect sealing at all times.
- Door remains open when at 90° for easy loading.
- An IoT ready device.

Options

- Exterior customizable.
- Reverse door.



Reliability



Hydrocarbons



Energy Saving



Customization

Technical Data

External dimensions (mm)	1435 x 512 x 850
Net weight (kg)	77
Internal net volume (Lt)	309
Capacity 33 cl cans / bot. 20cl (pcs)	435 / 348
24h energy consumption (kW/h)	2,17
Climatic class	CC2-K4 (32°C/65%HR)
Temperature range (°C)	+2 / +8

* (width x depth x height)

Refrigerant	R-600a
Voltage	230v
Frequency	50Hz
Refrigeration power (W)	167
Noise level (db)	53
Transport 13m truck	66