EF3-22MU



Our back-bar coolers are a reference in the international market because of its guality, reliability and thanks to our collaboration with the most prestigious beverages brands in this range for over 30 years.

Efficold`s equipment highlights for the low energy consumption and they are designed exclusively for our customers to enhance their brand at the sales point.

Features

- Four flat shelves.
- Four feet adjustable in height.
- Digital thermostat and automatic defrost.
- Automatic evaporation of defrost water.
- Low maintenance condenser.
- Double LED internal illumination (only on when door is open).
- Ecological injected polyurethane insulation free of CFCs, density 40kg/m³.
- Ultra low energy consumption.
- Low Noise level of 53dB(A).
- Self closing door system for perfect sealing at all times.
- Door remains open when at 90° for easy loading.
- An IoT ready device.

Options

- Exterior customizable.
- Reverse door.







Customization

1435 x 512 x 850

CC2-K4 (32°C/65%HR)

77

309

1,84

+2 / +8

435 / 348

Reliability

Internal net volume (Lt)

Climatic class

Capacity 33 cl cans / bot. 20cl (pcs)

24h energy consumption (kW/h)







Temperature range (°C)

* (width x depth x height)

Refrigerant	R-600a
Voltage	230v
Frequency	50Hz
Refrigeration power (W)	162
Noise level (db)	53
Transport 13m truck	66

efficold reserves the right to modify the characteristics of its products without prior notice

