# VAH-340-V



Our VAH showcases have been developed with the perspective of creating added value for the end customer in mind.

Thus, we have combined the guarantee and reliability of efficold, with options for customization and perfect product visibility, achieving the greatest possible impact at each point of sale.



Re

efficold reserves the right to modify the characteristics of its products without prior notice







eliability Hydrocarbons

Energy Saving Cus

#### Customization

## **Technical Data**

External dimensions (mm)	530 x 750 x 1960
Net weight (kg)	110
Internal net volume (Lt)	238
24h energy consumption (kW/h)	11,9
Refrigeration Power (W)	452
Temperature range (°C)	-24 / -14
* (width x depth x height)	

They are ideal for the preservation of products between -14°C and -24°C.

#### **Features**

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Triple glass door mounted on an aluminium profile and handle either inlaid on the side.
- Four shelves included.
- $\circ~$  Ecological injected polyurethane insulation free of CFCs, density 40kg /m  $^3.$
- Temperature control by digital thermostat with automatic defrost.
- Four rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system.
- $\circ\;$  Automatic evaporation of defrost water.
- Door with self-closing system.
- Unitary palletized.

### Options

- Ventilated or static cooling according to customer needs.
- Door lock.
- Customizable exterior.
- Logo illuminated on the glass.
- Customizable price tags.
- Energy management device (EMD).

Refrigerant	R-290
Voltage / frequency	230v / 50Hz
Lateral serigraphy dimensions (mm)	668 x 1926
Glass serigraphy dimensions (mm)	435 x 1480
Transport 40' container / 13m truck	54 / 69