

Fast Lane 1500

Las dimensiones del Fast Lane permiten ubicarle en múltiples zonas de supermercados y tiendas de alimentación.

Un producto que llamará la atención de cualquier comprador debido a su estilizado diseño, personalidad y fantástica iluminación.



Reliability



Hydrocarbons



Energy Saving



Customization

Features

- Interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle in the front.
- Four shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by analog thermostat.
- Four rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Door with self-closing.
- Low-maintenance condenser.
- Palletized four units per pallet.

Options

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).
- Door lock.

Technical Data

External dimensions (mm)	502 x 482 x 1510
Net weight (kg)	62
Internal net volume (Lt)	138
Capacity 33 cl cans / 50 cl pets (pcs)	180 / 90
24h energy consumption (kW/h)	-
Climatic class	CC2 (32°C/65%HR)

* (width x depth x height)

Temperature range (°C)	0 / +8
Refrigerant	R-600a
Voltage / frequency	230v / 50Hz
Front serigraphy dimensions (mm)	357 x 1476
Lateral serigraphy dimensions (mm)	496 x 266
Transport 40' container / 13m truck	84 / 104