

Especialmente diseñado para estar ubicado en la cabecera de góndola, el double sided cooler permite optimizar la visibilidad y el acceso a los productos.

Unos de los claros elementos de diferenciación de este producto es su potencial de branding. El cliente puede personalizarlo con dos marcas distintas y crear promociones combinadas.



Reliability



Hydrocarbons



Energy Saving



Customization

Features

- Double interior LED light vertically arranged to maximize the product visibility.
- Interior and exterior made of metal sheet that provide a great robustness.
- Double glass door mounted on an aluminium profile and handle either inlaid on the side.
- Three shelves included.
- Ecological injected polyurethane insulation free of CFCs, density 40kg /m³.
- Temperature control by digital thermostat with automatic defrost.
- Two rollers and two front feet adjustable in height.
- Uniform cold distribution thanks to the excellent design of the ventilated cooling system and its evaporator.
- Automatic evaporation of defrost water.
- Doors with self-closing and opening fixation system.
- Unitary palletized.

Options

- Exterior customizable.
- Printed and /or illuminated logo in the glass.
- Energy Management Device (EMD).

Technical Data

External dimensions (mm)	523 x 498 x 1543
Net weight (kg)	69
Internal net volume (Lt)	125
Capacity 33 cl cans / 50 cl pets (pcs)	120 / 60
24h energy consumption (kW/h)	1,66
Climatic class	CC1 (25°C/60%HR)
Temperature range (°C)	0 / +8

* (width x depth x height)

Refrigerant	R-600a
Voltage / frequency	230v / 50Hz
Front grid serigraphy dimensions (mm)	435 x 421
Lateral grid serigraphy dimensions (mm)	417 x 417
Front glass serigraphy dimensions (mm)	353 x 947
Lateral glass serigraphy dimensions (mm)	588 x 947
Transport 40' container / 13m truck	0 / 0